



Hewlett Packard
Enterprise

HPE 3PAR STORESERV 20000 STORAGE

3PAR StoreServ Storage



WHAT'S NEW

- Empower data at the speed of memory with the industry's first Tier-1 storage with Storage Class Memory (SCM) and NVMe
- Reduce troubleshooting and management headaches with HPE InfoSight Advanced Performance Analytics, available in HPE SSMC 3.4 management console
- Eliminate storage networking bottlenecks

OVERVIEW

Have Cloud or IT-as-a-Service (ITaaS) environments forced you to settle for Tier-1 storage that compromises your data center? HPE 3PAR StoreServ 20000 Storage is an enterprise flash array with more than 3.8M IOPS, sub-millisecond latencies, a 16x density advantage over the competition [1], and scalability of over 20 PB of usable capacity for massive consolidation – for block and file workloads as well as object access – with Quality of Service (QoS). The flash-optimized architecture features the HPE 3PAR Gen5 ASIC for silicon-based hardware acceleration,

and accelerate performance for all-flash with new HPE 3PAR 32Gb FC

including inline deduplication, compression, data packing, thin technologies and other compaction technologies that can reduce acquisition and operational costs without compromising performance. Configuration options are available for all-flash models and combined flash and HDD models. HPE 3PAR StoreServ 20000 also includes at no extra charge data protection with HPE Recovery Manager Central.

FEATURES

Accelerate Fiber Channel Performance for 3PAR all Flash storage

HPE 3PAR 9000/20000 32Gb FC HBA delivers up to 2X performance compared to the 16Gb 4 port FC HBA in a smaller port footprint for mixed workloads and FC port consolidation.

Resilient So You Can Consolidate with Confidence

The HPE 3PAR StoreServ 20000 Storage maintains 99.9999% availability with a complete set of persistent technologies within your Hewlett Packard Enterprise 3PAR array.

Consolidate with confidence and protect against interference from multiple partitions “noisy” neighbors by delivering consistent Quality of Service (QoS).

Achieve extreme data protection for a complete enterprise disaster recovery plan by extending peer persistence support for a third data center across geographical distances.

Simplify backup and restore with HPE Recovery Manager Central (RMC) for application-aware, storage-integrated data protection.

Futureproof to Support Hybrid and On-demand Computing

Get ready for what’s next with the HPE 3PAR StoreServ 20000 Storage emerging technologies, such as storage class memory (SCM) and Non-Volatile Memory Express (NVMe) to protect your investments.

Get All-Flash on premise for a low cost per GB per month, with HPE Flash Now Program.

Modernize your EMC®, HDS®, and IBM® storage infrastructure with painless, no-cost data migration. HPE 3PAR Online Import seamlessly moves data between any HPE 3PAR StoreServ array.

Automated SAN configuration with built-in target driven federated zoning, with HPE Smart SAN.

Flexible to Meet Unpredictable Business Demands

The HPE 3PAR StoreServ 20000 Storage supports the most rigorous, on-demand infrastructure with a virtually limitless, elastic pool of storage.

Runs workloads at the right cost and service level agreement (SLA) with one-click



workload balancing.

Slashes management overhead with unified management of block, file, and object access and storage that is self-configuring, self-provisioning, and self-optimizing.

Technical specifications

HPE 3PAR StoreServ 20000 Storage




Capacity	6 PB Raw 15 PB Useable Based on 3.84 TB cLMC SSDs and HPE 3PAR compaction technologies
Drive description	(1920) SFF SAS/MDL SAS/SSD or (1024) SFF/LFF SSD or (960) LFF MDL SAS
Enclosures	(96) 3PAR 12 Gb/sec SAS SFF Drive Enclosure (96) 3PAR 12 Gb/sec SAS LFF Drive Enclosure
Maximum drives per enclosure	24
Host interface	32 Gb/sec Fibre Channel (10) Ports per controller 16 Gb/sec Fibre Channel (20) Ports per controller or 10 GbE iSCSI/FCoE (10) Port per controller or 10Gb Ethernet (6)
Cache	51.6 TiB Maximum, depending on model
Storage controller	(8) 3PAR 6-core 2.5 GHz 20800 Controller Node (8) 3PAR 8-core 2.5 GHz 20850 Controller Node (4) 3PAR 8-core 2.5 GHz 20450 Controller Node (8) 3PAR 8-core 2.5 GHz 20840 Controller Node Maximum, depending on model
Availability features	Redundant power supplies, battery backup units, Mesh active controllers Persistent Cache, Drive sparing and Multiple OS instances.
Servers supported	Maximum, depending on model
Compatible operating systems	HP-UX HPE OpenVMS IBM AIX Microsoft Windows Hyper-V Microsoft Windows Server 2012 R2 Citrix XenServer Oracle Linux Oracle Enterprise Linux Oracle UEK Oracle Solaris Ubuntu Server Edition 12.04 LTS Red Hat Enterprise Linux (RHEL) VMware ESX and ESXi SLES11 SP3 Apple OS X Also includes Red Hat Virtualization, IBM Virtualization and SLES Virtualization



For additional technical information, available models and options, please reference the [QuickSpecs](#)

Make the right purchase decision.
Contact our presales specialists.

[Call for availability](#)



**Hewlett Packard
Enterprise**

HPE POINTNEXT

Access expertise at every step of your IT journey with [HPE Pointnext Services](#). [Advisory Services](#) focuses on your business outcomes and goals, to design your transformation and build a roadmap tuned to your unique challenges. Our [Professional](#) and [Operational Services](#) help speed up time-to-production and keep your IT stable and reliable.

Operational Services from HPE Pointnext Services

- [HPE Datacenter Care](#) helps modernize and simplify IT operations. Partner with an assigned account team, access technical expertise, an enhanced call experience gives you priority access, choose hardware and software support, implement proactive monitoring to help stay ahead of issues, and access HPE IT best practices and IP.
- [HPE Proactive Care](#) offers an enhanced call experience and helps reduce problems with personalized proactive reports and advice. This also includes collaborative software support for Independent Software Vendors (ISVs), (Red Hat, VMWare, Microsoft, etc.). [Read more](#)
- [HPE Foundation Care](#) helps when there is a problem and has a choice of response levels. Collaborative software support is included and provides troubleshooting help for ISVs running on your server. [Read more.](#)

Other related services

[Defective Media Retention](#) is optional and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

[HPE Service Credits](#) offers a menu of technical services, access additional resources, and specialist skills.

[HPE Education Services](#) provides comprehensive training designed to expand the skills of your IT staff and keep them up to speed with the latest technologies.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and support options.

HPE GREENLAKE

[HPE Greenlake](#) is HPE's market-leading IT as-a-Service offering that brings the cloud experience to apps and data everywhere – data centers, multi-clouds, and edges – with one unified operating model. HPE GreenLake delivers public cloud services and infrastructure for workloads on premises, fully managed in a pay per use model.

If you are looking for more services, like [IT financing solutions](#), please [explore them here](#).

[1] Based on publicly available information of six EMC VMAX 850 systems totaling 24 PB of usable SSD capacity as compared to the HPE 3PAR 20850 with 24 PB usable SSD capacity (using a 4:1 compaction ratio).

© Copyright 2020 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

IBM® is trademark of IBM Corporation in the United States and/or other countries; Apple® is a trademark of Apple Inc., registered in the U.S. and other countries; Hyper-V® is a registered trademark of Microsoft Corporation in the United States and other countries; Citrix® is a trademark and/or registered trademark of Citrix Systems, Inc. in the United States and other countries; Red Hat® Enterprise Linux® Red Hat is a trademark of Red Hat, Inc. in the U.S. and other countries. Linux is a registered trademark of Linus Torvalds; Ubuntu® is a registered trademark of Canonical Ltd; VMware® is a registered trademark of VMware, Inc. in the United States and/or other jurisdictions; Hyper-V® is a registered trademark of Microsoft Corporation in the United States and other countries; Oracle® is a trademark of Oracle Corporation in the U.S. and other countries.

Image may differ from the actual product
[PSN8295785USEN](#), June 06, 2020.